

Minifile Openlight



Serie di apparecchi da semi-incasso, a plafone e a sospensione per illuminazione diretta diffusa. Per sorgenti linear LED o lampade fluorescenti T16 seamless. Alimentazione elettronica integrata 50/60Hz 230/240V (versioni LED alimentate a 350/700mA). Disponibili come moduli finiti o come moduli da assemblare a sistema. Corpo in estruso di alluminio, finitura verniciata o anodizzata. Schermo diffusore in policarbonato opalino bianco e testate di chiusura laterali con sistema Light Proof. Grado di protezione IP40 o IP43 a seconda del tipo d'installazione.

Series of semi-recessed, ceiling-mounted or suspended fixtures for direct diffused lighting. For linear LED sources or T16 fluorescent seamless lamps. 230/240V 50/60Hz integrated electronic supply (LED versions fed at 350/700mA). Available both as default modules and as modules to be assembled in a system. Body in extruded aluminium, painted or anodized finish. Opal white polycarbonate diffuser and Light Proof system side-end caps. Degree of protection IP40 or IP43, according to the way that it is installed.

Minifile openlight




SEMINCASSO - SEMI-RECESSED



SOFFITTO - CEILING-MOUNTED



SOSPENSIONE - SUSPENSION



Anatomia di gamma - range anatomy

W mm	13W linear LED	20W linear LED	27W linear LED	36W linear LED	41W linear LED	1x14-24W T16 seamless	1x21-39W T16 seamless	1x28-54W T16 seamless	1+1x21-39W T16 seamless	1+1x28-54W T16 seamless
580										
593										
595										
893										
1140										
1193										
1420										
1700										
1778										
2278										

Versioni emergenza e dimmerabili + emergenza su richiesta - emergency and dimmable + emergency version on request

W mm	13W linear LED	20W linear LED	27W linear LED	36W linear LED	41W linear LED	1x14-24W T16 seamless	1x21-39W T16 seamless	1x28-54W T16 seamless	1+1x21-39W T16 seamless	1+1x28-54W T16 seamless
Emergency										
Emergency										
Dimmerabile + emergenza										
Dimmerabile + Emergency										

MODULI FINITI - DEFAULT MODULES
MINIFILE OPENLIGHT
 semi-incasso - semi-recessed



SEMINCASSO LED CON DIFFUSORE - SEMI RECESSED LED WITH DIFFUSER
 LINEAR LED CRI>80


L. mm	W	Lumen	K	COD.	COL.
580	1x13W	1600	3000	MO030	01 27
580	1x13W Dali/Touch&Dim	1600	3000	MO030D	01 27
860	1x20W	2040	3000	MO031	01 27
860	1x20W Dali/Touch&Dim	2040	3000	MO031D	01 27
1140	1x27W	3200	3000	MO032	01 27
1140	1x27W Dali/Touch&Dim	3200	3000	MO032D	01 27
1420	1x34W	3400	3000	MO033	01 27
1420	1x34W Dali/Touch&Dim	3400	3000	MO033D	01 27
1700	1x41W	4080	3000	MO034	01 27
1700	1x41W Dali/Touch&Dim	4080	3000	MO034D	01 27

Su richiesta disponibile la versione 4000K | On request available 4000K version
 Su richiesta versioni Emergenza vedi tabella pag.33 | Emergency version on request see table page 33

SEMINCASSO FLUO CON DIFFUSORE - SEMI RECESSED FLUO WITH DIFFUSER
 T16 80000000


L. mm	W	COD.	COL.
580	1x14-24W GS 230V	MO035	01 27
580	1x14-24W GS 230V Dali/Touch&Dim	MO035D	01 27
893	1x21-39W GS 230V	MO036	01 27
893	1x21-39W GS 230V Dali/Touch&Dim	MO036D	01 27
1193	1x28-54W GS 230V	MO037	01 27
1193	1x28-54W GS 230V Dali/Touch&Dim	MO037D	01 27
1778	1+1x21-39W GS 230V	MO038	01 27
1778	1+1x21-39W GS 230V Dali/Touch&Dim	MO038D	01 27
2378	1+1x28-54W GS 230V	MO039	01 27
2378	1+1x28-54W GS 230V Dali/Touch&Dim	MO039D	01 27

Su richiesta versioni Emergenza vedi tabella pag.33 | Emergency version on request see table page 33



- 01 BIANCO - WHITE
- 27 OSSIDATO ALLUMINIO - OXIDISED ALUMINIUM

MODULI FINITI - DEFAULT MODULES
MINIFILE OPENLIGHT
 soffitto - ceiling



SOFFITTO LED CON DIFFUSORE - CEILING MOUNTED LED WITH DIFFUSER
 LINEAR LED CRI>80


L. mm	W	Lumen	K	COD.	COL.
580	1x13W	1600	3000	MO020	01 27
580	1x13W Dali/Touch&Dim	1600	3000	MO020D	01 27
860	1x20W	2040	3000	MO021	01 27
860	1x20W Dali/Touch&Dim	2040	3000	MO021D	01 27
1140	1x27W	3200	3000	MO022	01 27
1140	1x27W Dali/Touch&Dim	3200	3000	MO022D	01 27
1420	1x34W	3400	3000	MO023	01 27
1420	1x34W Dali/Touch&Dim	3400	3000	MO023D	01 27
1700	1x41W	4080	3000	MO024	01 27
1700	1x41W Dali/Touch&Dim	4080	3000	MO024D	01 27

Su richiesta disponibile la versione 4000K | On request available version 4000K
 Su richiesta versioni Emergenza vedi tabella pag.33 | Emergency version on request see table page 33

SOFFITTO FLUO CON DIFFUSORE - CEILING MOUNTED FLUO WITH DIFFUSER
 T16 80000000

L. mm	W	COD.	COL.
580	1x14-24W GS 230V	MO025	01 27
580	1x14-24W GS 230V Dali/Touch&Dim	MO025D	01 27
893	1x21-39W GS 230V	MO026	01 27
893	1x21-39W GS 230V Dali/Touch&Dim	MO026D	01 27
1193	1x28-54W GS 230V	MO027	01 27
1193	1x28-54W GS 230V Dali/Touch&Dim	MO027D	01 27
1778	1+1x21-39W GS 230V	MO028	01 27
1778	1+1x21-39W GS 230V Dali/Touch&Dim	MO028D	01 27
2378	1+1x28-54W GS 230V	MO029	01 27
2378	1+1x28-54W GS 230V Dali/Touch&Dim	MO029D	01 27

Su richiesta versioni Emergenza vedi tabella pag.33 | Emergency version on request see table page 33



- 01 BIANCO - WHITE
- 27 OSSIDATO ALLUMINIO - OXIDISED ALUMINIUM



MODULI FINITI - DEFAULT MODULES
MINIFILE OPENLIGHT
 sospensione - suspension



SOSPENSIONE LED CON DIFFUSORE - SUSPENSION LED WITH DIFFUSER
 LINEAR LED CRI>80



L. mm	W	Lumen	K	COD.	COL.
580	1x13W	1600	3000	MO040	01 27
580	1x13W Dali/Touch&Dim	1600	3000	MO040D	01 27
860	1x20W	2040	3000	MO041	01 27
860	1x20W Dali/Touch&Dim	2040	3000	MO041D	01 27
1140	1x27W	3200	3000	MO042	01 27
1140	1x27W Dali/Touch&Dim	3200	3000	MO042D	01 27
1420	1x34W	3400	3000	MO043	01 27
1420	1x34W Dali/Touch&Dim	3400	3000	MO043D	01 27
1700	1x41W	4080	3000	MO044	01 27
1700	1x41W Dali/Touch&Dim	4080	3000	MO044D	01 27

Su richiesta disponibile la versione 4000°K | On request available version 4000°K
 Su richiesta versioni Emergenza vedi tabella pag.33 | Emergency version on request see table page 33

SOSPENSIONE FLUO CON DIFFUSORE - SUSPENSION FLUO WITH DIFFUSER
 T16 80000000

L. mm	W	COD.	COL.
585	1x14-24W G5 230V	MO045	01 27
585	1x14-24W G5 230V Dali/Touch&Dim	MO045D	01 27
893	1x21-39W G5 230V	MO046	01 27
893	1x21-39W G5 230V Dali/Touch&Dim	MO046D	01 27
1193	1x28-54W G5 230V	MO047	01 27
1193	1x28-54W G5 230V Dali/Touch&Dim	MO047D	01 27
1778	1x421-39W G5 230V	MO048	01 27
1778	1x421-39W G5 230V Dali/Touch&Dim	MO048D	01 27
2378	1x428-54W G5 230V	MO049	01 27
2378	1x428-54W G5 230V Dali/Touch&Dim	MO049D	01 27

Su richiesta versioni Emergenza vedi tabella pag.33 | Emergency version on request see table page 33



01 BIANCO-WHITE
 27 OSSIDATO ALLUMINIO-OXIDIZED ALUMINIUM

SISTEMI COMPONIBILI - MODULAR SYSTEMS
MINIFILE OPENLIGHT
 Sistema - System



PROFLO VUOTO SOFFITTO/SOSPENSIONE/SEMINCASSO - EMPTY PROFILE CEILING/SUSPENSION/SEM-RECESSED

L. mm	COD.	COL.
575	MO000.575	01 27
586	MO000.586	01 27
855	MO000.855	01 27
865	MO000.865	01 27
1135	MO000.1135	01 27
1188	MO000.1188	01 27
1415	MO000.1415	01 27
1695	MO000.1695	01 27
1773	MO000.1773	01 27
2373	MO000.2373	01 27
3000	MO000.3000	01 27
taglio a misura / custom cut	MO000.*	01 27



COPIA TESTATE SOFFITTO/SEMINCASSO/SOSPENSIONE - COUPLE OF CLOSURE HEADS CEILING/SEM-RECESSED/SUSPENSION VERSIONS

COD.	COL.
MO005	01 27

*Tramite questo codice è possibile ordinare il profilo in una lunghezza lineare non standard. Sostituire a " " la lunghezza desiderata in mm. Per ordinare un profilo con una o entrambe le estremità tagliate ad angolo 45° aggiungere alla misura la lettera "D" (taglio Destro) o "S" (taglio Sinistro). Seguire istruzioni riportate a pag.69. Per profili oltre 3 mt e massimo 6 mt le condizioni di trasporto sono da concordare. |
 *Through this code it's possible to order the profile in a not-standard linear length. Replace the " " with the desired length in mm. To order a profile with one or both ends 45° angle-cut add the letter "D" (right cut) or "S" (left cut) to the standard or custom length. Follow the instructions on page 69. For profiles de mas de 3 metros y m aximo 6 metros de longitud las condiciones de transportes son a acordar. |

01 BIANCO - WHITE
 27 OSSIDATO ALLUMINIO - OXIDIZED ALUMINIUM

SISTEMI COMPONIBILI - MODULAR SYSTEMS
MINIFILE OPENLIGHT
 Sistema - System



REGLETTE LED 24W/m² - 24W/m² LED 24W/m²



LINEAR LED CRI > 80

L. mm	W	Lumen	K	COD.
560	1x13W	1360	3000	RLM3M01
560	1x13W Dali/Touch&Dim	1360	3000	RLM3M01D
560	1x13W	1360	4000	RLM4M01
560	1x13W Dali/Touch&Dim	1360	4000	RLM4M01D
840	1x20W	2040	3000	RLM3M02
840	1x20W Dali/Touch&Dim	2040	3000	RLM3M02D
840	1x20W	2040	4000	RLM4M02
840	1x20W Dali/Touch&Dim	2040	4000	RLM4M02D
1120	1x27W	2720	3000	RLM3M03
1120	1x27W Dali/Touch&Dim	2720	3000	RLM3M03D
1120	1x27W	2720	4000	RLM4M03
1120	1x27W Dali/Touch&Dim	2720	4000	RLM4M03D
1400	1x34W	3400	3000	RLM3M04
1400	1x34W Dali/Touch&Dim	3400	3000	RLM3M04D
1400	1x34W	3400	4000	RLM4M04
1400	1x34W Dali/Touch&Dim	3400	4000	RLM4M04D
1680	1x41W	4080	3000	RLM3M05
1680	1x41W Dali/Touch&Dim	4080	3000	RLM3M05D
1680	1x41W	4080	4000	RLM4M05
1680	1x41W Dali/Touch&Dim	4080	4000	RLM4M05D
2240	1x55W	5440	3000	RLM3M07
2240	1x55W Dali/Touch&Dim	5440	3000	RLM3M07D
2240	1x55W	5440	4000	RLM4M07
2240	1x55W Dali/Touch&Dim	5440	4000	RLM4M07D

Alimentatore incluso. Su richiesta versioni Emergenza vedi tabella pag.33 | Included ballast Emergency version on request see table page 33

SELV

SISTEMI COMPONIBILI - MODULAR SYSTEMS
MINIFILE OPENLIGHT
 Sistema - System



REGLETTE FLUO SEAMLESS - REGLETTE FLUO SEAMLESS

T16 SEAMLESS

L. mm	W	COD.
585	1x14-24W G5 230V	LTM034
585	1x14-24W G5 230V Dali/Touch&Dim	LTM034D
885	1x21-39W G5 230V	LTM035
885	1x21-39W G5 230V Dali/Touch&Dim	LTM035D
1185	1x28-54W G5 230V	LTM036
1185	1x28-54W G5 230V Dali/Touch&Dim	LTM036D
1770	1+1x21-39W G5 230V	LTMB34
1770	1+1x21-39W G5 230V Dali/Touch&Dim	LTMB34D
2370	1+1x28-54W G5 230V	LTMB35
2370	1+1x28-54W G5 230V Dali/Touch&Dim	LTMB35D

Su richiesta versioni Emergenza vedi tabella pag.33 | Emergency versions on request see table page 33

STRIP BOBINA DA 5 METRI - STRIP LED 5 METERS ROLL

L. mm	W/m ²	IP	LED/m ²	lm/m ²	K	CUT	COD.
5000	9,6W 24V	IP20	120	930	3000	50 mm	ST10.30.5
5000	14,4W 24V	IP20	60	1110	3000	100 mm	ST15.30.5
5000	19W 24V	IP20	240	1680	3000	25 mm	ST20.30.5
5000	9,6W 24V	IP65	120	930	3000	50 mm	ST10.30.5IP
5000	14,4W 24V	IP65	60	1110	3000	100 mm	ST15.30.5IP

DISPOSITORE PER STRIP LED - HEATSINK FOR STRIP LED

L. mm	COD.
1000	LTMC.1000
2000	LTMC.2000
3000	LTMC.3000
taglio a misura/custom cut	LTMC.....*

* Insieme a questo codice è possibile ordinare il profilo in una lunghezza lineare non standard. Sostituire a "....." la lunghezza desiderata in mm. Per ordinare un profilo con uno o entrambe le estremità tagliate ad angolo 45° aggiungere alla misura la lettera "D" (taglio Destro) o "S" (taglio Sinistro). Seguire istruzioni riportate a pag. 70. Per profili oltre i 3 mt e massimo 6 mt le condizioni di trasporto sono da concordare.
 * Through this code it's possible to order the profile in a not-standard linear length. Replace the "....." with the desired length in mm. To order a profile with one or both ends 45° angle-cut add the letter "D" (right cut) or "S" (left cut) to the standard or custom length. Follow the instructions on page 70. For profiles of more than 3 meters and maximum 6 meters of length the conditions of transport are to be agreed.

SISTEMI COMPONIBILI - MODULAR SYSTEMS


MINIFILE OPENLIGHT
Sistema - System



DIFFUSORE - DIFFUSER

L. mm	COD.
573	MO004.573
586	MO004.586
853	MO004.853
886	MO004.886
1133	MO004.1133
1186	MO004.1186
1413	MO004.1413
1693	MO004.1693
1771	MO004.1771
2371	MO004.2371
3000	MO004.3000
taglio a misura / custom cut	MO004.____*

*Tramite questo codice è possibile ordinare il profilo in una lunghezza lineare non standard. Sostituire a "____" la lunghezza desiderata in mm. Per ordinare un profilo con una o entrambe le estremità tagliate ad angolo 45° aggiungere alla misura la lettera "D" (taglio Destro) o "S" (taglio Sinistro). Seguire istruzioni riportate a pag. 70. Per profili oltre i 3 mt e massimo 6 mt le condizioni di trasporto sono da concordare.]
*Through this code it's possible to order the profile in a not standard linear length. Replace the "____" with the desired length in mm. To order a profile with one or both ends 45° angle-out add the letter "D" (right cut) or "S" (left cut) to the standard or custom length. Follow the instructions on page 70. Para perfiles de mas de 3 metros y maximo 6 metros de longitud las condiciones de transportes son a acordar.]



STAFFA SINGOLA SEMINCASSO UNA OGNI METRO, MINIMO 2 - FIXING BRACKET FOR TRIMLESS SEM-RECESSED VERSION. ONE EVERY METER, 2 PIECES MINIMUM

COD.
MO007


SISTEMI COMPONIBILI - MODULAR SYSTEMS

MINIFILE OPENLIGHT
Sistema - System



COPPIA GIUNTI LINEARI - LINEAR JOINTS COUPLE

COD.
LTM046



COPPIA GIUNTI ANGOLARI - ANGLE CONNECTORS COUPLE

COD.
per composizioni planari | for flat assembling LTM046.90
per composizioni parete/soritto | for wall/ceiling assembling LTM046.90P



KIT SOSPENSIONE SINGOLO IN ACCIAIO L.2000 MM. UNO OGNI 1,5 MT. MINIMO 2 - SINGLE STEEL SUSPENSION KIT L.2000MM. ONE EVERY 1,5 MT. 2 PIECES MINIMUM

COD.
LTM047



KIT ALIMENTAZIONE COMPLETO DI ROSONE BIANCO L.2000 MM. - POWER CABLE KIT WITH CEILING WHITE CANOPY L.2000 MM.

L. mm	DM.	COD.	COL.
2000	3X0,75	LTM048.3	01
2000	4X0,75	LTM048.4	01
2000	5X0,75	LTM048.5	01
2000	7X0,75	LTM048.7	01

This document was created with Win2PDF available at <http://www.win2pdf.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.
This page will not be added after purchasing Win2PDF.