

GENIUS BASIC ASYMMETRICAL




GENIUS WALL WASHER IN 80 mm DI SPESSORE.

La variante di Genius Slope destinata al mondo Contract è un prodotto compatto, con possibilità di installazione in intercapedini di soli 80 mm, a soffitto e parete come segnapassi. Genius Basic Slope è un apparecchio da incasso a scomparsa totale per interni, realizzato in Coral® per questa nuova versione. Il foro luce asimmetrico, con asse inclinato di 40°, garantisce una emissione luminosa di 540 lm, con possibilità di effetto wall-washer. La parte elettrica è direttamente estraibile dal foro luce, grazie a un sistema che facilita l'estrazione e la sostituzione della sorgente LED, senza la necessità di alcuna botola di ispezione e tantomeno di interventi invasivi in caso di manutenzione.

GENIUS WALL WASHER IN A THICKNESS OF 80 mm.

The "Slope" version of Genius, designed for the Contract world is a very compact product which can be installed in a cavity measuring only 80 mm (3.15"), ceiling and wall mounted as a path lighter. Genius Basic Slope is a totally recessed luminaire for indoor use, made in Coral® for this new variant. The asymmetrical light emission hole, with a 40° angled axis, guarantees a light emission of 540 lm, with possibility of a wall-washer effect. The electrical part can be removed through the light hole, thanks to a mechanism that makes it easy to pull the LED light source out and replace it, so there is no need for any inspection hatch, nor for invasive maintenance operations.



CODE COMPOSITION

1865.00 4 R 24 E _ WD	<i>light colour</i>	
	27	2700K
	30	3000K
	40	4000K
1866.00 4 R 24 E _ ND	<i>light colour</i>	
	27	2700K
	30	3000K
	40	4000K
example of code composition	1865.00 4 R 24 E 30 WD	

TECHNICAL FEATURES

Code	1865.00 XX	1866.00 XX
Type	Downlight 90°	Downlight 90°
Material	00: Coral®	00: Coral®
Weight	0.65 Kg	0.65 Kg
Mounting	Ceiling recessed	Ceiling recessed
IP rating	IP20	IP20
Insulation class	III	III
Control gear	Remote constant current electronic driver (not included)	Remote constant current electronic driver and inverter (included)
Cut out for plasterboard	100 x 100 mm	100 x 100 mm
Lamp type	LED 700 mA Vf:6.5 VDC	LED 700 mA
Lamp wattage	1 x 4.5W	1 x 4.5W
Luminous efficacy	540 lm - 3000K	540 lm - 3000K
Light distribution	Wide beam 24°	Wide beam 24°
Fitting	-	-
Light colour	White 3000K White 2700K 4000K (on request)	White 3000K White 2700K 4000K (on request)
Light hole	Ø 20 mm	Ø 20 mm
Voltage connection	By driver (optional)	220-240V · 50/60Hz
CRI	>90	>90
Emergency	-	1 hour
Energy efficiency class	A++	A++
Note	On request available dimmable PUSH or DALI, remote installation.	On request available dimmable PUSH or DALI, remote installation.

OPTIONAL ACCESSORIES

product code	optional code	description	info
1865.00 XX	H8700.E	Constant current electronic driver. Remote installation	Suitable for n°3 code 1865.00 XX - 700 mA
	BR1865LT	Brick box	Dimensions L: 195 mm; W: 140 mm; D: 160 mm
1866.00 XX	BR1866LT	Brick box	Dimensions L: 195 mm; W: 140 mm; D: 160 mm