



| Description

Outdoor pendant luminaire consisting of a satinised optical polymer diffuser (two sizes available), anodised aluminium heat sink. Power supply unit excluded, can be supplied with constant current or constant voltage via a special converter.

General specifications

tipo di installazione mounting type	sospensione suspension
materiali materials	alluminio, PMMA steel, aluminum, PMMA
finiture finishes	bianco opaco RAL 9010, nero opaco RAL 9005, oro, bronzo, rame, brunito, corten, ottone spazzolato, custom matt white RAL 9010, matt black RAL 9005, gold, bronze, copper, burnished, corten, brushed brass, custom
overall dimensions	Ø25x83 - Ø25x83
peso weight	0,05±0,08kg (testa) 0,05±0,08kg (headlight)
grado di protezione IP IP rating	IP65
grado di protezione IK IK rating	IK06

| Electrical specifications

gruppo di alimentazione power supply unit	non incluso not included
potenza power	1,5W
alimentazione power supply	350mA
classe di isolamento insulation class	III

Light source

@ 4000K, Ta = 25°, Tj = 25°

lampada lamp	LED ad alta potenza high power LED
temperatura di colore colour temperature	2700 - 3000 - 4000K
indice di resa cromatica colour rendering index	≥90
vita media average life	50000h L80 B10
consistenza cromatica colour consistency	2 SDCM
efficienza luminosa luminous efficiency	95lm/W
flusso luminoso luminous flux	142lm

Gruppo ottico | Optical group

diffusore diffuser	PMMA satinato sandblasted PMMA
----------------------	----------------------------------

