



Description

IP66 outdoor adjustable headlight with an aluminium body and rod, available in three wattages with remote power supply. The mechanically machined stainless steel joint also guarantees a rotation of the lamp body of 340° on the vertical axis. A layer of polyurethane resin, with high transparency, deposited on the optical unit ensures the necessary IP protection in the most unfavorable orientations. It is available in five photometric distributions.

General specifications

tipo di installazione <i>mounting type</i>	paletto <i>bollard</i>
materiali <i>materials</i>	alluminio <i>aluminum</i>
finiture <i>finishes</i>	bianco opaco RAL 9010, nero opaco RAL 9005, oro, bronzo, rame, brunito, corten, ottone spazzolato, custom <i>matt white RAL 9010, matt black RAL 9005, gold, bronze, copper, burnished, corten, brushed brass, custom</i>
dimensioni <i>overall dimensions</i>	Ø26x100mm
peso <i>weight</i>	-
grado di protezione IP <i>IP rating</i>	IP66
grado di protezione IK <i>IK rating</i>	IK06

Electrical specifications

gruppo di alimentazione <i>power supply unit</i>	remoto <i>remote</i>
alimentazione <i>power supply</i>	corrente costante, 50/60Hz <i>constant current, 50/60Hz</i>
tensione operativa LED <i>LED operating voltage</i>	11,2Vdc
dimmerazione <i>dimming</i>	su richiesta <i>on demand</i>
classe di isolamento <i>insulation class</i>	III

Light source

@ 4000K, Ta = 25°, Tj = 25°

lampada <i>lamp</i>	LED ad alta potenza <i>high power LED</i>
temperatura di colore <i>colour temperature</i>	2700 - 3000 - 4000K
indice di resa cromatica <i>colour rendering index</i>	≥90
vita media <i>average life</i>	50000h L80 B10
consistenza cromatica <i>colour consistency</i>	2 SDCM

I (mA)	Ø (lm)	P (W)	light efficiency (lm/W)
350	926	2x4	116
500	1254	2x6	105

