




### File Flex hand rail



Lighting element made of extruded 6060 aluminium for indoor use. Wall installation for use as a handrail; direct and diffused light emission with one indirect component given by the asymmetric shape of the co-extruded white silicone diffuser, complete with rill 16 W/m LED, cri>90; installation with special ones hooks that can be positioned freely on the profile (maximum suggested center distance 1500 mm) consisting of double sliding steel element that allows the recovery of any wall discrepancies; possibility of differentiation of the finish between profile and connections a wall; the power cable entry is provided at disappeared in the wall connection; version with handle a straight terminal or "turned" at 90 degrees with joint aspizza double angle 45°; powder coated finish epoxy or liquid for Premium finishes. IP44 standard version, also available in version Outdoor IP66.





## **SPECIFICHE PRODOTTO**

Metodo di installazione	Parete
Sorgente luminosa	Led
Potenza assorbita	10 W/mt
Temperatura colore K	2700/3000/3500/4000/TW/ RGBW
Indice di resa cromatica CRI	>90
Finitura	Verniciata
Flusso sorgente	1300 lm/mt
Tolleranza colore MacAdam	3
Durata media stimata	3SDCM 50000h L80 B10 Ta 25°C
Alimentatore/trasformatore	Non incluso
Protocollo	Vedi alimentatore
Classe di efficienza energetica	D
Dimensione	34x34xL fino a 6000 mm
Grado IP	IP44/IP66
Classe di protezione	Apparecchio in classe III

