



# CONVEX



## FISSO | FIXED



taglio per incasso / recessed hole dimension  $\varnothing$  75  
 spazio per passaggio alimentatore / necessary space to insert driver  $\varnothing$  75



LED		W	mA	$\varnothing$	H	Kg	lm product/beam 3000K	CODE
$\varnothing$ 84	F27°	8	300	84	90	0,35	860 / 860	CV018.9 ●● / ##
	W46°	12	350	84	90	0,35	1285 / 1285	

LED		W	mA	$\varnothing$	H	Kg	lm product/beam 3000K	CODE
	F27°	12	350	84	110	0,35	1285 / 1285	CV019.9 ●● / ##
	W46°	18	500	84	110	0,35	1575 / 1575	

GU10		W	$\varnothing$ mm	H mm	Kg	CODE
		50	84	110	0,21	CV020

NOTE: COMPLETARE CON DRIVER | DRIVER NOT INCLUDED    DISPONIBILI ANCHE VERSIONI 2700 / 4000K E FINITURA NERA / 02 | AVAILABLE VERSION 2700 / 4000K AND BLACK / 02 | FINISHING



## ACCESSORIO PER TRASFORMARE CONVEX IN VERSIONE TRIMLESS ACCESSORY TO TRANSFORM CONVEX IN TRIMLESS RECESSED



$\varnothing$  ESTERNO / EXTERNAL 100 mm

CODE  
CV030



### VERSIONI DISPONIBILI / AVAILABLE VERSION

● <b>KELVIN</b>	● <b>FASCIO / BEAM</b>	/ ## <b>FINITURA   FINISHING</b>
27 2700K	F Flood 27°	□ / 01 bianco   white
30 3000K	W Wide 46°	■ / 02 nero   black
35 3500K		
40 4000K		

COMPOSIZIONE CODICE: xxx.x ●● / ##  
 HOW TO CREATE THE CODE: F1000.8 275 / 01

CODE  
**F1000.8**    ●    ●    / ## finishing  
 base code    kelvin    beam

250 | 350 | 500 DRIVERS VEDI | SEE P.452