

# I-SQUARE

## RECESSED




FISSO | FIXED



INCLINABILE | ADJUSTABLE



### FISSO | FIXED




NOTE: COMPLETARE CON DRIVER | DRIVER NOT INCLUDED - DISPONIBILI ANCHE VERSIONI 2700 / 4000K E FINITURA NERA / 02 | AVAILABLE VERSION 2700 / 4000K AND BLACK / 02 | FINISHING

taglio per incasso / recessed hole dimension 77X77



LED		LWX		H	Kg		Im product / beam 3000K		CODE	
W	mA				F27°	W46°				
8	250	84.5X84.5		95	0,35	860	860			ISO13.9 ●● / ##
12	350	84.5X84.5		95	0,35	1285	1285			



LED		LWX		H	Kg		Im product / beam 3000K		CODE	
W	mA				F27°	W46°				
12	350	84.5X84.5		115	0,35	1285	1285			ISO14.9 ●● / ##
18	500	84.5X84.5		115	0,35	1575	1575			

GU10		LWX		Hmm	Kg		CODE	
W								
50		84.5X84.5		94	0,21			ISO15

### INCLINABILE | ADJUSTABLE




NOTE: COMPLETARE CON DRIVER | DRIVER NOT INCLUDED - DISPONIBILI ANCHE VERSIONI 2700 / 4000K E FINITURA NERA / 02 | AVAILABLE VERSION 2700 / 4000K AND BLACK / 02 | FINISHING

taglio per incasso / recessed hole dimension 77X77



LED		LWX		H	°	Kg		Im product / beam 3000K		CODE	
W	mA					F27°	W46°				
8	250	84.5X84.5		95	30	0,35	860	860			ISO16.9 ●● / ##
12	350	84.5X84.5		95	30	0,35	1285	1285			



LED		LWX		H	°	Kg		Im product / beam 3000K		CODE	
W	mA					F27°	W46°				
12	350	84.5X84.5		115	30	0,35	1285	1285			ISO17.9 ●● / ##
18	500	84.5X84.5		115	30	0,35	1575	1575			

GU10		LWX		Hmm	Kg		CODE	
W								
50		84.5X84.5		94	0,21			ISO17

#### VERSIONI DISPONIBILI / AVAILABLE VERSION

##### ● KELVIN

- 27 2700K
- 30 3000K
- 35 3500K
- 40 4000K

##### ● FASCIO / BEAM

- F Flood 27°
- W Wide 46°

##### /## FINITURA | FINISHING

- /01 bianco | white
- /02 nero | black

#### COMPOSIZIONE CODICE: xxx.x ●● / ##

HOW TO CREATE THE CODE: F1000.8 27S / 01

CODE  
**F1000.8** ●● / ## — finishing  
 base code kelvin beam

DRIVERS VEDI | SEE P.452 59